


tesa® 75007

75 µm double-sided, tackified acrylic adhesive tape with PET scrim for mounting and lamination applications in automotive interiors



Product Description

tesa® 75007 is a conformable, tackified acrylic adhesive tape with a thickness of 75 µm, reinforced by a PET scrim. This tape has especially been developed for all kinds of demanding lamination and mounting applications. It shows a high humidity resistance and edge repulsion resistance. Due to its low VOC property it is particularly designed to meet automotive interior requirements.

tesa® 75007 is suitable for laminating all kinds of foam, fleece, and felt substrates and mounting light interior components.

Product Features

- Highly conformable to follow difficult 3-D shapes
- Low VOC (acc. GB 27630) – no critical substances detectable
- Reinforcement supports converting efficiency
- Very good humidity resistance
- High initial tack and excellent repulsion resistance
- Secure mounting even to nonpolar plastics (PP) and composites (recycled materials)
- Very good initial adhesion to a wide variety of interior substrates

Application Fields

tesa® 75007 is suitable for mounting and lamination applications.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Type of liner **glassine**

Total thickness **75 µm**

Backing material **none**

Type of adhesive **tackified acrylic**

Color **transparent**

Color of liner **brown/blue logo**

Properties / Performance Values

Suitable for die cutting **Yes**

Additional Information

According to VDA278 analysis, our 75007-tapes does not contain any single substances restricted by the drafted GB regulations (China) as well as the indoor concentration guideline by Health, Labour and Welfare Ministry (Japan). Adhesion vaules to PVC, PP, ABS, PC, PET, PS, PE are not part of the product specification

